



PROPIEDADES CON ENGARGOLADO A 90 GRADOS					
CALIBRE	PESO POR	Ix+ cm4/m	Sx+ cm3/m	Ix- cm4/m	Sx- cm3/m
26	5.126	21.44	3.55	20.62	4.41
24	5.923	20.45	5.48	29.77	6.08
22	8.316	39.33	7.53	38.92	7.74
20	9.91	47.39	9.3	47.25	9.35

CAPACIDAD DE CARGA ADMISIBLE (KG/M2) (UNIFORMEMENTE DISTRIBUIDA)									
TIPO DE APOYO	CALIBRE	SEPARACION ENTRE APOYOS							
		0.75	0.90	1.05	1.20	1.35	1.50	1.65	1.80
SIMPLE 	26	660	528	386	293	230			
	24			596	454	357	288	239	
	22				621	489	396	327	274
	20					606	489	406	337
DOBLE 	26		640	474	362	288	230		
	24			650	498	318	318	264	
	22				630	406	406	332	279
	20					489	489	401	337
TRIPLE 	26		689	547	420	332	269		
	24			757	582	459	371	308	
	22					582	469	391	327
	20						572	469	396



Guadalajara +52 (33) 3629 9989 / Monterrey +52 (81) 8212 9023

www.gharmansolutions.com