



STYROFOAM™ Brand UTILITYFIT™ XPS 15 PSI

Extruded Polystyrene Foam Insulation

1. PRODUCT NAME

STYROFOAM™ Brand UTILITYFIT™ XPS
15 PSI™ Extruded Polystyrene Foam
Insulation

2. MANUFACTURER

The Dow Chemical Company
Dow Building Solutions
200 Larkin Center, 1605 Joseph Drive
Midland, MI 48674
1-866-583-BLUE (2583)
Fax 1-989-832-1465
www.insulateyourhome.com

3. PRODUCT DESCRIPTION

Basic Use

STYROFOAM™ Brand UTILITYFIT™ XPS
15 PSI™ Extruded Polystyrene Foam
Insulation is a versatile, utility-grade
product manufactured for applications that
require a high R-value* and outstanding
moisture resistance without the need for
high compressive strength.

STYROFOAM™ Brand UTILITYFIT™ XPS
15 PSI Insulation is designed for use
when a Type X, or lower-compressive
strength, product is needed. If the superior
properties of a Type IV 25 psi product
are not required, STYROFOAM™ Brand
UTILITYFIT™ XPS 15 PSI Insulation is a
good choice for your application.

4. TECHNICAL DATA

Applicable Standards

STYROFOAM™ Brand UTILITYFIT™ XPS 15
PSI™ Insulation meets ASTM C578, Type X
– Standard Specification for Rigid Cellular
Polystyrene Thermal Insulation. Applicable
standards include:

- C518 – Standard Test Method for
Steady State Thermal Transmission
Properties by Means of the Heat Flow
Meter Apparatus

- D1621 – Standard Test Method for
Compressive Properties of Rigid
Cellular Plastics
- C272 – Standard Test Method for
Water Absorption of Core Materials for
Structural Sandwich Constructions
- E96 – Standard Test Methods for Water
Vapor Transmission of Materials
- D696 – Standard Test Method for
Linear Thermal Expansion of Plastics
Between -30°C and 30°C with a
Vitreous Silica Dilatometer

Code Compliances

STYROFOAM™ Brand UTILITYFIT™ XPS
15 PSI™ Insulation complies with the
following codes:

- Meets IBS/IRC requirements for foam
plastic insulation; see ICC-ES NER-699
- ICBO-ES ER-2257
- BOCA-ES RR 21-02
- Underwriters Laboratories, Inc. (UL)
Classified, see Classification
Certificate D369

Contact your Dow sales representative
or local authorities for state and local
building code requirements and related
acceptances

TYPICAL PHYSICAL PROPERTIES

STYROFOAM™ Brand UTILITYFIT™ XPS
15 PSI™ Insulation exhibits the physical
properties characteristics indicated in
Table 2 when tested as represented.

Prolonged exposure to ultraviolet radiation
may cause the surface of STYROFOAM™
Brand UTILITYFIT™ XPS 15 PSI Insulation
to become faded and dusty. A light-colored,
opaque protective covering should be used
if excessive solar exposure is expected.
The surface degradation will have no
measurable effect on the insulating value
of the plastic foam unless the deterioration
is allowed to continue until actual foam
thickness is lost. Since the dust would
impair the performance of adhesives
and finishes, the dusty surface should be
brushed off before these products
are applied.

ENVIRONMENTAL DATA

STYROFOAM™ Brand UTILITYFIT™ XPS 15
PSI™ Insulation is manufactured with
a zero ozone-depleting (ODP), no-VOC
(volatile organic compound) foaming
agent technology. STYROFOAM™ Brand
UTILITYFIT™ XPS 15 PSI Insulation is
reusable in many applications.

TABLE 1: Sizes, R-values and edge treatments for STYROFOAM™ Brand UTILITYFIT™ XPS 15 PSI™ Extruded Polystyrene Foam Insulation

Nominal Board Thickness ⁽¹⁾ , in .	R-value ⁽²⁾	Board Size, FT	Edge Treatment
1.0	5.0	2 × 8, 4 × 8, 4 × 9	Square Edge Tongue and Groove, Scoreboard
1.5	7.5	2 × 8, 4 × 8, 4 × 9	Square Edge Tongue and Groove, Scoreboard
2.0	10.0	2 × 8, 4 × 8, 4 × 9	Square Edge Tongue and Groove, Scoreboard
3.0	15.0	2 × 8, 4 × 8, 4 × 9	Square Edge Tongue and Groove, Scoreboard

(1) Not all product sizes are available in all regions. Additional product sizes are available by custom order. Consult your Dow sales representative about other sizes and lead-time requirements.

(2) Aged R-value at 1" cured foam @ 75°F mean temperature. R-value expressed in ft²•h•°F/Btu. R-value determined by ASTM C518 using the aging process in ASTM C1289 (90 days @ 140°F).

Fire Protection

STYROFOAM™ Brand UTILITYFIT™ XPS 15 PSI insulation is combustible; protect from high heat sources. Local building codes may require a protective or thermal barrier. For more information, consult MSDS, call Dow at 1-866-583-BLUE (2583) or contact your local building inspector.

5. INSTALLATION

Boards of STYROFOAM™ Brand UTILITYFIT™ XPS 15 PSI™ Insulation are easy to handle, cut and install. Contact a local Dow representative or access the literature library at www.dowstyrofoam.com/architect or www.insulateyourhome.com for more specific instructions.

6. AVAILABILITY

STYROFOAM™ Brand UTILITYFIT™ XPS 15 PSI™ Insulation is manufactured in several locations across North America and is distributed through an extensive network. For more information, call 1-800-232-2436.

7. WARRANTY

Not applicable.

8. MAINTENANCE

Not applicable.

9. TECHNICAL SERVICES

Dow can provide technical information to help address questions when using STYROFOAM™ Brand UTILITYFIT™ XPS 15 PSI insulation. Technical personnel are available to assist with any insulation project. For technical assistance, call 1-866-583-BLUE (2583).

Technical personnel are available to assist with any insulation project. For technical assistance, call 1-866-583-BLUE (2583).

10. FILING SYSTEMS

- www.dowstyrofoam.com/architect
- www.insulateyourhome.com
- www.sweets.com

TABLE 2: Typical Physical properties (U.S.) of STYROFOAM™ Brand UTILITYFIT™ XPS 15 PSI™ Extruded Polystyrene Foam Insulation

Property and Test Method	Value
Thermal Resistance per inch, ASTM C518 @ 75°F mean temp., ft ² •h•°F/Btu, R-value ⁽¹⁾ , min.	5.0
Compressive Strength ⁽²⁾ , ASTM D1621, psi, min.	15
Water Absorption, ASTM C272, % by volume, max.	0.3
Maximum Use Temperature, °F	165
Coefficient of Linear Thermal Expansion, ASTM D696, in/in•°F	3.5 × 10 ⁻⁵

(1) Values are consistent with the criteria of ASTM C578 and the FTC R-value rule (16 CFR Part 460). R means resistance to heat flow. The higher the R-value, the greater the insulating power.

(2) Vertical compressive strength is measured at 10 percent deformation or at yield, whichever occurs first. Since STYROFOAM™ Brand Extruded Polystyrene Foam Insulations are visco-elastic materials, adequate design safety factors should be used to prevent long-term creep and fatigue deformation. For static loads, 3:1 is suggested. For dynamic loads, 5:1 is suggested. Contact Dow for design recommendations.



a proud partner of



The Dow Chemical Company

Dow Building Solutions
200 Larkin • Midland, MI 48674

US

Technical Information: 1-866-583-BLUE (2583)
Sales Information: 1-800-232-2436

dowbuildingsolutions.com

NOTICE: No freedom from any infringement of patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries or regions. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DOW. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

Dow Polyurethane Foam Insulation and Sealants

CAUTION: When cured, these products are combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F (116°C). For more information, consult (Material) Safety Data Sheet ((M)SDS) call Dow at 1-866-583-BLUE (2583) or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada. When air sealing buildings, ensure that combustion appliances, such as furnaces, water heaters, wood burning stoves, gas stoves and gas dryers are properly vented to the outside. See website: <http://www.epa.gov/iaq/homes/hip-ventilation.html>. In Canada visit: <http://archive.nrc-cnrc.gc.ca/eng/ibp/irc/bsi/83-house-ventilation.html>.

STYROFOAM™ Brand Spray Polyurethane Foam contains isocyanate, hydrofluorocarbon blowing agent and polyol. Read all the instructions and (M)SDS carefully before use. Wear protective clothing (including long sleeves), gloves, goggles and proper respiratory protection. Supplied air or an approved air-purifying respirator equipped with an organic vapor sorbent and a P100 particulate filter is required to maintain exposure levels below ACGIH, OSHA, WEEL or other applicable limits. Provide adequate ventilation. Contents under pressure. STYROFOAM™ Brand SPF should be installed by a trained SPF applicator.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including Dow can give assurance that mold will not develop in any specific system.